

AC22E-01

AC charger for electric vehicles

Preliminary



RELIABLE AND SAFE

- Integrated with 6mA DC fault current detection
- IP65 protection suitable for both indoor and outdoor usage



SMART MANAGEMENT

- Beyond charging – maximum usage of solar energy together with Sungrow hybrid inverter *
- Capable of load management and balancing to prevent overload **
- Control and visualization via App



FLEXIBLE APPLICATION

- Available in two power outputs 3-phase 11kW and 22kW
- Capable of OCPP 1.6J communication
- Different charging modes to fit all needs ***



USER FRIENDLY

- Integrated with MID-certified meter to accurately measure electricity usage
- Support various options for authentication
- Time-saving installation by wall-mounting or with stand column options



Technical parameters	AC22E-01
AC Input	
Grid voltage	3 / N / PE, 230 V / 400 V
Nominal grid frequency	50 Hz / 60 Hz
Earthing system	TT / TN
Max. input current	32 A
Standby self-consumption	< 6.5 W
AC Output	
Max. charging power	22 kW / 11 kW (configurable)
Max. charging voltage	230 V / 400 V
Max. charging current	32 A / 16 A (configurable)
Protection & Function	
Integrated DC fault current detection	Yes, 6 mA
Overload protection	Yes
Over-temperature protection	Yes
Surge protection	Yes
Ground fault monitoring	Yes
ALM (Adaptative load management)	Yes
Automatic phase switching	Yes
User interface	
Display	LED indicator and App
Authentication	Plug & Play / RFID-card / iSolarCloud App / iEnergy Charge App
Firmware update	OTA
RFID system	Mifare ISO 14443 A
Energy metering	MID-certified meter (optional)
Metering accuracy	Class B
Charging mode	OCPP / Plug & play / EMS by iEnergyCharge Eco charging / Fast charging / Scheduled charging / Customized charging by iSolarCloud
Communication interface	RS485 (to inverter / meter) WLAN / Ethernet / 4G (to cloud)
Communication protocol (charger-to-CSMS)	OCPP 1.6 J
Mechanical data	
Dimensions (W*H*D)	214 mm * 346 mm * 125 mm
Weight	< 6.65 kg
Installation method	Wall-mounting (default) Stand column (optional)
AC cable specification	Cross-section 5 * 6 mm ²
Charging cable length	7 m
Charging connector	Type 2
Environmental data	
Enclosure rating	IP65
Mechanical impact protection	IK10
Operating ambient temperature range	-30 °C - 50 °C
Allowable relative humidity range	5 % - 95 % (non-condensing)
Max. operating altitude	3000 m
Cooling method	Natural convection
General data	
Compliance	EN 300 328, EN 300 330, EN 301 489-1 / 3 / 17 / 52, EN 301 908-1 / 13, EN 50663, EN 50665, EN IEC 61851-1, EN IEC 61851-21-2, EN IEC 62311, EN 62479
Warranty	3 years (standard)

* Additional smart meter required.

** Compatible with Sungrow hybrid inverter SHRT / SHRT-20.

*** Only available with Sungrow hybrid inverter in iSolarCloud.

